



Laia myTeam TP1

Laia myTeam TP1 will end the costly investments that need to be made to conduct FullHD video conferencing. Its Full HD PTZ Camera and 20x optical zoom with "Crystal Clear" image quality and AV production camera quality movement will ensure a clear image in all your communications.

Size is no longer an issue. With Laia myTeam TP1 you will turn any meeting room into the perfect place for your video conferences. Regardless of its size, our TP1 can handle it.

FHD

Full HD PTZ equipment

x2

H264 ++ data sharing and dual HDMI output for 2 monitors

WiFi

Ethernet and WiFi (optional)

WiFi

WiFi Microphone (optional)

Intuitive user interface



FEATURES

Package	<ul style="list-style-type: none"> • HD codec (FullHD camera) x 1 • Omnidirectional microphone (pickup distance > 5m) x 1 • Remote control x 1 • Power Adapter x 1 • HDMI cable (1.5m) x 2 • XLR jack to 3.5mm jack cable x 1 • User manual (Quick Start, Quick Installation Guide) x 1
Standards and protocols	ITU-T H.323, IETF SIP, Up to 8Mb / sec. H.261, H.263, H.263 ++, H.264, H.264 SVC, H.264 High Profile
Audio standards and protocols	G.711, G.722, G.722.1, G.722.1C, AAC-LD, G.723.1, G.726, G.728, SILK
Dual stream	ITU-T H.239, BFCP
Other standards	H.221, H.225, H.235, H.241, H.245, H.281, H.350, H.460, T.140, DTMF
Network protocols	TCP / IP, DHCP, SSH, HTTP, HTTPS with SSL / TLS, RTP, RTCP, RFC3261, RFC3264, RFC2190, RFC3407, RFC2833, RFC4585 (RTP / AVPF), SNTP, ARP
Resolution	<ul style="list-style-type: none"> • 1080P at 512Kbps • 720P at 384Kbps • 4CIF / 4CIF at 128Kbps • SIF / CIF / QSIF / QCIF / SQSIF / SQCIF at 64Kbps
Video content resolution	<ul style="list-style-type: none"> • VGA (640x480), SVGA (800x600), XGA (1024x768), WXGA (1280x768), WUXGA (1280x800), 1280x960, SXGA (1280x1024), 1360x768, 1366x768, 1440x900, XGA + (1400x1050), 1600x900, 1600x10, 720p (1280x720), 1080p (1920x1080) • Coding Resolution: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080 • Output: 800x600, 1024x768, 1280x1024, 1280x720, 1920x1080
Dual Stream	720P
Camera	<ul style="list-style-type: none"> • Input: 1080P • Sensor: 2.07 M pixels, 1 / 2.7 CMOS • Lens: 20x optical zoom • Horizontal angle: 60° • PTZ: horizontal +/- 170°, vertical -30° - + 90° • Automatic white balance, focus and exposure. • Remote camera control. • Mirror / flip bracket • 10 presets
Other video features	PIP (Picture in Picture), PoP (Picture outside Picture)
Audio	<ul style="list-style-type: none"> • AEC (Echo Cancellation) • AGC (Automatic Gain Control) • ANS (Acoustic noise suppression) • Lip-Audio Synchronization
Net	FEC (Forward Error Correction), ARQ (Automatic Repeat-reQuest) etc. 10/100 Mbps. WiFi (Optional)
Security	<ul style="list-style-type: none"> • H.235 (AES) Encryption communication. • Administrator password, SSH / HTTPS
Traversal firewall	H.460.18 / 19, H.460.23 / 24, ICE
Audio input	1 x 3.5mm line-in jack, 1 x 3.5mm mic-in jack
Audio outputs	1 x 3.5mm line-out jack, 1 x HDMI audio output
Video inputs	1 x HDMI 1 x camera
Video output	2 x HDMI
Other interface	1 x RS232: 3pin Phoenix jack
USB and RJ45	2 x USB2.0 (USB flash disk and micro USB) 10 / 100Mbps
Languages	More than 24, including English and Spanish
Specific benefits	<ul style="list-style-type: none"> • Audio associated with the presentation • Supports 'SameView' • Timing for on and off • Automatic standby mode • Supports DNS SRV • PIP: 1/16, voice activation, etc. • Split output for 2 monitors. • Network agenda • MCU 3 + 1 (optional) • Remote control: H.224, H.281 • Configuration and administration through LAN port and remotely through web browser. • Wi-Fi (optional) • 1000 entries local agenda • LDAP and H.350
Dimensions	<ul style="list-style-type: none"> • Dimensions (L x W x H): 240mm x 144mm x 160mm • Package dimensions (L x W x H): 285mm x 235mm x 230mm • Net Weight: 1.7Kg • Box Weight: 2.5Kg
Feeding	<ul style="list-style-type: none"> • Voltage: AC 100V - 240V, DC 12V • Frequency: 50 / 60Hz • Consumption: 18W
Environmental specification	<ul style="list-style-type: none"> • Operating temperature: 0 ° C to 40°C • Humidity: 10% to 80% • Noise: <46 dBA SPL • Lighting: 5 lux • Recommended lighting > 300 lux
Certifications	CCC, CE, RoHS, WEEE, FCC

Headquarters:

Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- Spain

After-sale service:

C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - Spain



MYTEAM - VIDEOCONFERENCE