



Laia B&H PC Pro

The Laia B&H PC Pro captures 1080p Full HD video at 30 frames per second. In addition, together with its 3D noise reduction algorithm, the Laia PC Pro will manage to significantly eliminate image noise, achieving sharp productions even in tight light spaces.

Thanks to its 2 omni-directional digital echo cancellation microphones, the audio quality in such a small camera surprises: perfect for personal use. It also features ePTZ functionality with Laia Cam Control software.



Video FullHD 30 fps, with a professional lens to offer a crystal clear and fluid video



Autofocus facial recognition *



Compatible with all PC, Mac and Chromebook-based video conferencing solutions



2 digital pro microphones, with echo cancellation and noise reduction



ePTZ camera with Laia Cam Control

Compatible with:



About Cloud goFacing or Pexip services.



THE PERFECT USB CAMERA FOR PERSONAL USE THANKS TO ITS LARGE LENS 88° WIDE ANGLE AND BUILT-IN DIGITAL MICROPHONES

PROFESSIONAL WARRANTY

FEATURES

Sensor	1 / 2.7", CMOS, Effective Pixel: 2.07M
Scanning mode	Progressive
Lens mount	M12
Lens	Focus: f = 2.8mm, FOV: 88 °
Minimum illumination	0.05 Lux @ (F1.8, AGC ON)
Trigger	1 / 30s - 1 / 10000s
White balance	Auto, Indoor, Outdoor, One Press, Manual
Camera mount	Clamp holder
Digital noise reduction	2D, 3D digital noise reduction
Backlight compensation	Supported

FEATURES USB

Operating system	Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher. MacOS 10.10 or higher Google™ Chromebook™ Version 29.0.1547.70 or higher Linux
Processor	2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port
Color / Compression System	H.265 / H.264 / MJPEG
Video format	50fps / 30fps / 25fps, 720p @ 30fps / 25fps, 960x540p @ 30fps / 25fps, 640x360p @ 30fps / 25fps
USB video communication protocol	UVC 1.0 - UVC 1.5

INPUT/OUTPUT INTERFACE

USB interface	1xUSB 2.0: Type A.
---------------	--------------------

GENERAL SPECIFICATIONS

Privacy option	Privacy cap to cover our lens
Tripod mount	Possibility of mounting on tripod or similar
Input voltage	5V (USB Power Supply)
Current consumption	300mA
Operating temperature	-10 ° C - 40 ° C (14 ° F - 104 ° F)
Storage temperature	-40 ° C - 60 ° C (-40 ° F - 140 ° F)
Energy consumption	1.5W
Size	118x37.2x30.8mm
Net weight	93g
MTBF	30000h

Headquarters:
Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- Spain

After-sale service:
C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - Spain



B&H - BUSINESS AND HOME