



Laia Cute 10x

Laia Cute 10X will be the perfect option to use in any meeting room, regardless of the video conferencing service you use. In addition, thanks to its 10X optical zoom you can capture all the important details for your professional video calls.

Its impressive FullHD image from its 1 / 2.8 "CMOS sensor with 1920 x 1080 resolution and up to 30ip coupled with its autofocus technology will allow you to enjoy professional video conferencing from the first moment.



Resolution is up to 1920x1080 with a frame rate of up to 30 fps



10X optical zoom with autofocus technology



Multiple control protocols: supports VISCA, Pelco-D, Pelco-P and automatic recognition protocol



User can choose to use IR remote control or wireless remote control



Supports up to 255 presets (10 presets by remote control)

Compatible with:



RESOLUTION UP TO 1920X1080
WITH A FRAME RATE
UP TO 30 FPS

PROFESSIONAL WARRANTY

3 year "Prime support" warranty 24 hrs advanced replacement

FEATURES

Image sensor	1 / 2.9 inch high quality CMOS sensor
Effective Pixels	2.07MP, 16: 9
Video format	1920 x 1080P @ 30 fps / 25fps; 1280 x 720P @ 30fps / 25fps; 1024 x 576P @ 30fps / 25fps; 960 x 540P @ 30fps / 25fps; 800 x 448P @ 30fps / 25fps; 640 x 360P @ 30fps / 25fps; 320 x 176P @ 30fps / 25fps
Optical lens	10X f = 4.34mm ~ 41.66mm optical lens
Vision angle	8.8 ° ~ 68.8 °
Iris	F1.85 - F2.43
Digital zoom	10X
Low illumination	0.5Lux (F1.8, AGC ON)
DNR	2D & 3D Digital noise reduction
White balance	Auto / Manual / One Push // 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K
Focus	Auto / Manual / One press
Electronic trigger	Auto / Manual
BLC	On / Off
WDR	OFF / Dynamic level adjustment
Video settings	Brightness, Color, Saturation, Contrast, Sharpness, Black and White Mode, Gamma Curve
SNR	≥55dB

INTERFACE AND PROTOCOL

Video output	USB 2.0
Video compression	H.265, H.264, MJPG
Control port	RS232 (Circuit), RS485
Control protocol	Protocol: VISCA / Pelco - D / Pelco - P
Power supply	HEC3800 Outlet (DC12V) with PoE
Power adapter	AC110V-AC220V input, DC12V / 1.5A output
Power input	DC12V ± 10% , 1A (Max)
Consumption	12W (max)

USB FEATURES

Operating system	Windows 7, Windows8, Windows10, Mac osx, Linux
Video compression	H.265, H.264, MJPG
USB communication protocol	UVC

PTZ PARAMETERS

Pan / tilt rotation	-170 ° ~ +170 ° , - 30 ° ~ + 90 °
Pan / tilt speed control	0.1 ~ 60 ° / seconds, 0.1 ~ 30 ° / seconds
Preset speed	Pan: 60 ° / Second, Tilt: 30 ° / Second
Number of presets	255 Presets (10 by remote control)

OTHER PARAMETERS

Working voltage	12V
Working current	0.25A (max)
Energy consumption	2.5W (max)
Temperature during operation	-10 ° C ~ + 50 ° C, 20% ~ 80%
Storage temperature	-10 ° C ~ + 60 ° C, 20% ~ 95%
Dimensions	156.8mm x 112.6mm x 139.5mm
Package weight	1 KG approximately
Use	Only inside
Package	12V / 1.5A power supply, remote control, manual, Warranty card and USB 2.0 cable
Optional gadgets	Frame (additional cost)

Headquarters:
Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- Spain

After-sale service:
C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - Spain



CUTE FAMILY - USB HDMI CAMERA