



Laia B&H UP 4K

Laia B&H UP 4K is a video conference device integrated with 4 array microphones and 4K wide-angle cameras. It supports HD audio and video calls and it is easy to deploy and operate, which is suitable for daily meetings, remote education, remote training and other application scenarios. It also has facial recognition.

Manufactured with avant-garde high-quality materials, the Laia B&H UP 4K presents itself as one of the most stylish "all-in-ones" on the market. A sober design accompanied by perfect technology for professional video conferencing.



4K camera with 120 degrees of view and wide-angle shooting for a clear image



Use of Full-Duplex that allows a more natural two-way communication



New AUCTOPUS® processing algorithm that allows coverage of up to 180°



Facial recognition



Mechanically adjustable lens



AV BAR WITH 4K CAMERA, FACIAL RECOGNITION, SPEAKER AND MICROPHONES FOR VIDEO CONFERENCING

PROFESSIONAL WARRANTY

FEATURES

Video	Includes lens, image sensor, digital signal processing chip, USB interface controller.
Microphone	4 omnidirectional microphones with a response frequency of 100Hz-24000Hz and a sensitivity of 22dB @ 1kHz (0dB = 1V / Pa). Includes broadband, speakers, digital microphone, echo and noise suppression processing, audio signal processing and control unit plus control by USB interface unit.
USB	USB Type-C
Feeding	Power adapter
Speaker	2-inch antimagnetic horn 4Ω8W 100-24000Hz
Interface	USB Type-C with DC interface
Power	DC 12V / 2A @ 100 ~ 240VAC, 50 / 60Hz
Lenses	1 / 2.8", fixed focus with 120 degrees of vision
Image sensor	CMOS image sensor 1/2.5", 8.5M pixels
Audio	384 ms echo cancellation Dynamic noise reduction Full-Duplex 180° audio pickup range DSP audio processing
Image transfer rate	3840x2160 MJPG @ 30FPS, 3840x2160 H264 @ 30FPS, 1920x1080 YUV @ 5FPS
F-number	F2.4
Object distance	50CM 500CM
Function	Support real-time communication Audio for software HD video calls
Operating system	Windows 8 / Windows 7 / Windows 10 / Windows XP etc. / MAC OS X 10.7 and higher
LED indicator	Blue / White: working status Red: microphone and speaker are off
Recommendations	Temperature: 5° ~ 44° Humidity: 20 ~ 85% non-condensing Noise level: <48db Storage temperature: -10° ~ 55° Reverberation time: <0.5 seconds
Product Execution Standard	YD / T 993-1998 GB / T 9254-2008 GB 4843.1-2011
Dimensions	42 cm x 7 cm x 7 cm

Headquarters:

Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- Spain

After-sale service:

C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - Spain



B&H - BUSINESS AND HOME