









Laila Broadcaster Follower

The camera that meets you

Main Features

Laila Broadcaster Follower	
12X Optical + 16x digital Zoom	
3G-SDI, Ethernet RJ45: 2 cameras	
2 wired LAN, Audio In.	
Up to 1080p 60fps	
Extremely silent & smooth PTZ cam.	
Up to 255 presets.	
Remote control: IR, 2.4G Wireless, RS-232, Visca, Pelco-D / P, RJ45...	
TV Studio Camera Quality, for corporate environments	



OUR PRODUCTION CAMERAS ARE COMPATIBLE WITH ALL PLATFORMS



BROADCASTER RANGE- PRODUCTION

PROFESSIONAL WARRANTY

3 year "Prime support" warranty 24 hrs advanced replacement

Laila Broadcaster Follower

CAMERA	
Image sensor	Panasonic 1/2.7 Inch High Quality HD CMOS Sensor
Effective Pixels	2.07MP, 16:9 2.07MP, 16:9
Video format	1080P60/50/30/25/59.94/29.97 ,1080i60/50/59.94,720P60/50/30/25 / 59.94 /2 9.97
Optical zoom	12x Optical Lens f=4.7~47mm
View angle	2.9°(tele)~55.4°(wide)
Iris	F1.8 – F2.8
Digital zoom	x10
Minimum Illumination	0.5Lux(F1.8, AGC ON)
DNR	2D&3D Digital Noise Reduction
White balance	Auto / Manual/ one push //3000K/4000K/5000K/6500K
Focus	Auto / manual
Aperture	Auto / manual
Electronic Shutter	Auto / manual
BLC	On / Off
WDR	OFF/ Dynamic Level Adjustment
Video adjustment	Brightness, Color, Saturation, Contrast, Sharpness, Gamma curve
SNR	>55dB
PANORAMIC CAMERA	
Sensor	Sensor 1/3 inch high quality HD CMOS sensor. Effective Pixels 2.1 megapixel
Lens manual focus	Lens manual focus
View angle (D/H/V)	122/98/73
INTERFACES & PROTOCOLS	
Video interface	2 x 3G-SDI HDMI
Network interface	2 X 100M network interface (10/100), Support VISCA protocol control through IP port.
Network protocol	RTSP, RTMP, ONVIF, GB/T28181; Support VISCA Control Protocol, Support Remote Update and Reset
Video stream	Dual stream
Video compression	H.265, H.264 Y MJPEH
Control signal interface	RS232
Control protocol	Protocol:VISCA/Pelco-D/Pelco-P;Baud Rate: 115200/9600/4800/2400bps
Audio input interface	A-in: Double track 3.5mm linear input;
Audio compression format	AAC, MP3, G.711A
Power supply	HEC3800 Outlet(DC12V)
Pan/tilt Rotation	-170°~+170°, -30°~+90°
Pan/tilt controller speed	0.1 ~100°/Second, 0.1~45°/Second
Preset speed	Pan: 100°/Second,Tilt: 45°/Second
Preset numbers	255 Points Preset(10 points By Remote Controller)
Power adapter	Input AC110V-AC220V, output DC12V/2.5A Output DC12V +/-10% POE Power supply opt.
Power consumption	18W(Max)
Storage temperature/humidity	-10°C~+40°C, 20%~95%
Working temperature/humidity	-10°C~+50°C, 20%~80%
Dimension	254mmX144mmX174mm
Weight	1.54 Kg
Usage	Indoor only
Package	12V/1.5A Power supply, Remote Controller, Manual, Warranty Card
Accessories optional	Wallmount



Headquarters:

Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- España

After-sale service:

C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - España



BROADCASTER RANGE- PRODUCTION