



Laia Cute 12x/30x



Laia Cute 12X/30X is the perfect camera for any meeting room or auditorium, regardless the used technology. Thanks to the "crystal clear" sensor and optical zoom up to 30x, you will get an incredible image quality.

The spectacular FullHD image offered by its CMOS-Panasonic sensor of 1/2.8" and up to 60fps with autofocus technology, making our Laia Cute possibly, the highest quality camera in its segment.



Optical Zoom 12x to 30x (depending on model)



USB 3.0 (2.0), HDMI and RJ45 PoE



Up to 1080p 60 fps with USB 3.0



Memorize up to 255 camera positions



Automatic gyroscope for your business environments

Compatible with:



POSSIBLY THE BEST CAMERA USB, HDMI & ETHERNET OF THE WORLD

PROFESSIONAL WARRANTY

3 year "Prime support" warranty 24 hrs advanced replacement

FEATURES	CUTE 12X/30X
Image sensor	1/2.8 CMOS-Panasonic high quality sensor
Resolution	5.0 MP sensor 2.07MP, effective 16.9
Video format	HDMI/SDI: 1080P60,1080P50,1080P30,1080P25,720P60,720P50,1080P59,1080P29,97.720P59,94 USB 3.0: 1920X1080i/1280X720i/1024X576/800X600/800X448/640X360/640X480/480X270/320X180@30/25/20/15/10/5 fps
Optical zoom	12X/30X for Cute 12X/30X
Vision angle	6.3-72.5 for Cute 12X and 2.34-65 for Cute 30X
Iris	F1.8-F2.4 for Cute 12X y F1.6-F4.7 for Cute 30X
Low illumination	0.5 Lux (F1.8, AGC ON)
DNR	2D&3D Digital noise reduction
White balance	Auto / Manual / One touch / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K
Focus	Auto / Manual / One touch
Electronic trigger	Auto / Manual
BLC	On / Off
WDR	OFF / Dynamic level adjustment
Video settings	Brighness, Colour, Saturation, Contrast, Sharpness, Black and white mode and Gamma curve
SNR	≥50dB
INTERFACE AND PROTOCOL	
Video output	HDMI, LAN, USB 3.0, (USB 2.0 é É à y)
Video stream	Dual stream out
Audio output	HDMI, LAN, USB3.0
Video Compression	LAN Interface: H.265, H.264, Dual stream output USB3.0 interface: Main stream supports YUY2, MJPEG, H.264, NV12, H.265 Secondary stream support YUY2, MJPEG, H.264, NV12
LAN	LAN (10/100/1000 BASE TX) , PoE
Network protocol	RTSP RTMP, ONVIF, GB/T28181; Compatible with VISCA protocol. Remote update and restart
Control port	RS232, RS485
Control protocol	Protocol: VISCA/Pelco-D/Pelco-P;Baud Rate:115200/9600/4800/2400bps
Power supply	HEC3800 Outlet(DC12V) with PoE
Power adapter	Input AC110V AC220V, Output DC12V/2.5A
Power input	DC12V±10%, 1A(Max)
Consumption	12W (max)
USB FEATURES	
Pan/tilt rotation	-170°-+170°, -30°-+90°
Presets Speed	Pan: 100° sec, Tilt:45° sec
Numbers of presets	255 presets (10 with remote control)
Gyroscopic	Automatic gyroscope
OTHER PARAMETERS	
Temperature during operation	-10°C-+50°C, 20%-80%
Storage temperature	-10°C-+60°C, 20%-95%
Dimensions	180mm x 115mm x 149mm
Weight	1.15 Kg
Use	Inside
Package	12V/2A Power supply,remote control, manual, warranty card, 1.5m USB cable and RS232 control cable
Warranty	3 advance warranty years extendable up to 5 years

Headquarter:
Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- Spain

After-sales service:
C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Seville - Spain

