



Laia Cute 10x Black/White

Laia Cute 10x Black/White will be the perfect option to use in medium video conference rooms, regardless of the video conferencing service you use. In addition, thanks to its 10X optical zoom you can capture all the important details for your professional video calls.

Its impressive FullHD image from its HD CMOS sensor with 2.07 effective megapixels for high-quality images up to 1920x1080 resolution with its autofocus technology will allow you to enjoy professional video conferencing from the first moment.



At the same time support two streams of stream output



Full-featured USB interface



1080P Full HD



H.264 Slice/
H.264 SVC
encoding support



The camera can be controlled using RS232



HIGH-QUALITY HD CMOS SENSOR WITH 2.07 EFFECTIVE MEGAPIXELS FOR HIGH-QUALITY IMAGES UP TO 1920X1080

PROFESSIONAL WARRANTY

3 year "Prime support" warranty 24 hrs advanced replacement

FEATURES

Video System	1080P, 720P, 540P, 480P, 360P, 240P etc.
Sensor	1/2.8", CMOS, Effective Pixel: 2.07M
Scanning mode	Progressive
Lens	10x, f4.7mm ~ 46.3mm, F1.8 ~ F2.8
Digital zoom	16x
minimal illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White balance	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Manual
Backlight compensation	Support
Digital noise reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal angle of view	58.5° ~ 6.5°
Vertical angle of view	35.1° ~ 3.6°
Horizontal rotation range	±170°
Pan speed range	2.7° ~ 35.7°/s
Tilt speed range	2.7° ~ 31.5°/s
H&V flip	Support
Image freeze	Support
Number of preset	255
Preset accuracy	0.1°

USB FEATURED

Operate system	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color system / compression	YUV 4:2:2 / H.264 / MJPEG
Video format	"H.264 AVC: max to 1080P@30fps H.264 SVC: max to 1080P@30fps MJPEG: max to 1080P@30fps"

USB video communication protocol	UVC 1.1- 1.5
UVC PTZ	Support

INPUT / OUTPUT INTERFACE

USB interface	1xUSB2.0: Type B female jack
Communication interface	1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P
Power supply	JEITA type (DC IN 12V) or USB - PoC*

GENERIC SPECIFICATION

Input voltage	DC 12V
Current consumption	0.5A (Max)
Operating temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power consumption	6W (Max)
MTBF	>30000h
Size	141.3mm x 153mm x 163.6mm
Net Weight	1.153 KG

*Valid only with original USB.

Headquarters:
Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- Spain

After-sale service:
C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - Spain



CUTE FAMILY - USB HDMI CAMERA