



Laia myTeam Sharer P/N: MTS-100SY

Laia myTeam Sharer is designed to facilitate your video conferences and presentations. It allows you to connect wirelessly and with a single click various devices to your personal computer, from cameras to microphones and external speakers. All in one.

It is compatible with AirPlay and Miracast from mobile devices and its automatic wireless IP connection will allow you to connect any computer. In addition, myTeam Sharer can communicate via myTeam Sharer/Dongle and myTeam Sharer/mini Dongle, making it the best Plug & Play device on the market.

Hybrid meetings have never been so easy!



BYOM wireless video conferencing and BYOD wireless presentation



Screen presentation for up to 4 participants at the same time



Mirroring via Windows, macOS, Android or Chromecast, Miracast and AirPlay



Video quality up to 4K60 via HDMI connection



PROFESSIONAL WARRANTY

3 years of "Prime support" warranty with 24 hrs advanced replacement

GENERAL

Windows 10/ 11 connections	MTS-series Dongle wireless Transmitters / myTeamSharer App for Windows / Miracast / Chromecast
macOS device connections	MTS-series Dongle wireless Transmitters / myTeamSharer App for macOS / AirPlay / Chromecast
Mobile device connections	App Android / AirPlay / Miracast / Chromecast
Maximum Video Input Resolution (wireless)	1080p60. Via MTS-series Dongle wireless Transmitters, myTeamSharer App for Windows&macOS and Airplay for IOS devices
HDMI Output & Resolution	1x HDMI 2.0 3840x2160@60/30 Hz, 1920x1080@60Hz, 1280x720@60Hz
HDCP version	HDCP 1.4, HDCP 2.0
Simultaneous Ethernet connections (RJ45) / WLAN	Up to 30 Up to 16
Splitscreen	4 + 14. Up to 4 simultaneously (4 main windows+14 thumbnail windows), adjustable layout
Audio input	MTS-series Dongle wireless Transmitters myTeamSharer App AirPlay Miracast Chromecast USB SpeakerPhone
Audio output (analog)	1x3.5 mm jack
WIFI Band / Bandwith / Estándar	2.4 / 5 GHz up to 1200 Mbit/s IEEE 802.11b/g/n/ac
WIFI antennas	2x2 MIMO + 1x1 MIMO (Miracast)
Safety standard	WiFi: WPA PSK, WPA2 PSK / Video transmission encrypted with AES-256 bit + RSA1024 bit
USB 2.0	(Type C) 1x (front), (Type A) 1x (front)
USB 3.0	(Type C) 1x (rear), 5V / 1.5 A max. (max. 20 Watt via all USB 3.0 connections) (Type A) 3x (rear), 5V / 1.5 A max. (max. 20 Watt via all USB 3.0 ports)
Touch-back / USB-HID support	Yes, e.g. for use in conjunction with interactive displays (touchscreens), whiteboards or projectors
LAN ports	1 x 1000 MBit/s with PoE+, RJ45 / 1x 100 MBit/s. RJ45
PoE	Standard PoE+ - IEEE802.3at
Control ports	Network: Web GUI, Telnet / RS232: 1x 3-pin euroblock (rear)
Compatible transceivers	MTS-101DG Dual USB-A/C minidongle and MTS-102DG USB-C Touch&Play dongle
DC Power voltage	12V PoE+
Power consumption	max. 30 W
Dimensions and weight	220 x 120 x 41. Including antenna: 220 x 120 x 145 1Kg
Supply accesories	1 x MTS-101DG, Dual USB-A/C minidongle 1 x AC-DC adaptor, 12V-3Amp, with exchangeable plugs (Euro AV, UK) 3 x antennas 1 x Phoenix 3 pin terminal 2 x Wall mounting bracket and 4 x fixing screws



Headquarters:
Po. Europa, 26 Pta. 1 Of.3
S.S. de los Reyes 28703
Madrid- España

Post sales service:
C/Brújula, 4 Pol. Ind. PISA
41927 Mairena del Aljarafe
Sevilla - España

